

低床式重荷重用キャスター

新型車輪 出来ました！！

1. 優れた走行性！！

タイヤ部がウレタン製の為、走行時床面に傷を付け難い製品です。

2. 優れた耐久性！！










ホイール部がアルミダイキャスト製で耐久性に秀でています。










詳しい寸法は
裏面をご確認下さい！






















低床式重荷重用キャスター アルミホイールウレタン車











金具=三価ユニクロ仕上

■ HG型・HSG型 自在車 プレート式										
品番	車輪									
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	daN (kgf)
HG-65	AU アルミホイールウレタン(B入)車	65	38	92	90×90	71×71	10.5	22	57	300 (306.0)
HG-75		75		106					61	320 (326.4)
HSG-65		65		90	82×82	63×63	8.8		57	300 (306.0)
HSG-75		75		100					61	300 (306.0)

■ HG-S型 自在車 プレート式 ストッパー付										
品番	車輪									
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	daN (kgf)
HG-65	AU S アルミホイールウレタン(B入)車	65	38	92	90×90	71×71	10.5	22	67	300 (306.0)
HG-75		75		106						320 (326.4)

■ HR型 固定車 プレート式										
品番	車輪									
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	daN (kgf)
HR-65	AU アルミホイールウレタン(B入)車	65	38	92	111×67	91×47	10.5			300 (306.0)
HR-75		75		106						123×72

■ HT型 自在車 ねじ込み式											
品番	車輪										
		(mm)	(mm)	(mm)			(mm)	(mm)	(mm)	(mm)	daN (kgf)
HT-65	AU アルミホイールウレタン(B入)車	65	38	93	M16	2	40	30	22	57	150 (153.0)
HT-75		75		107	M20	2.5	40			61	160 (163.2)

■ HT-S型 自在車 ねじ込み式 ストッパー付											
品番	車輪										
		(mm)	(mm)	(mm)			(mm)	(mm)	(mm)	(mm)	daN (kgf)
HT-65	AU S アルミホイールウレタン(B入)車	65	38	93	M16	2	40	30	22	67	150 (153.0)
HT-75		75		107	M20	2.5	40				160 (163.2)