



Wheel Diameter (D[mm])	Product No.	Wheel Material	Load Capacity [daN (kgf)]	Wheel Width (W[mm])	Mounting Height (H[mm])	Mounting Base (A×B[mm])	Mounting Dimensions (X×Y(X'×Y') [mm])	Hole Diameter (P[mm])	Eccentricity (E[mm])	Turning Radius (R[mm])		
150	WJ-150	Rubber(Including B)	200(204.0)	40	198	120×120	94×94(87×87)	11	40	115		
	NRJ-150											
	WEJ-150	Conductive Rubber(Including B)										
	WOJ-150	Oil Resistant Rubber(Including B)										
	WJ-150-G	Grey Rubber(Including B)										
	NRJ-150-G											
	MCBJ-150	Monomer Cast Nylon(Including B)										
	UWJ-150	PU(Including B)									300(306.0)	38
	GUJ-150										200(204.0)	40
	UWEJ-150	Antistatic PU(Including B)									300(306.0)	38
PHJ-150	Heat Resistant Phenol	200(204.0)	40									
200	WJ-200	Rubber(Including B)	250(255.0)	43	250	140×140	115×115(105×105)	11.5	56	156		
	WEJ-200	Conductive Rubber(Including B)										
	WOJ-200	Oil Resistant Rubber(Including B)										
	WJ-200-G	Grey Rubber(Including B)										
	MCBJ-200	Monomer Cast Nylon(Including B)										
	UWJ-200	PU(Including B)									400(408.0)	42
	GUJ-200										250(255.0)	43
	UWEJ-200	Antistatic PU(Including B)									400(408.0)	42
250	AWJ-250	Rubber(Including B)	400(408.0)	60	305	160×160	125×125	14	70	195		
	AUJ-250	PU(Including B)	600(612.0)	45								

- Light Duty LIGHTSTAR
- Medium Duty MIDDLESTAR
- Heavy Duty HEAVYSTAR
- Low-Profile Heavy Duty SHORTSTAR
- Leveling LOCKSTAR
- Stainless Steel STAINLESTAR
- Towing LEADSTAR
- Shock Absorbing SMOOSTAR
- Silence SILENTSTAR
- Office Equipment OFFICESTAR


Wheel Type




GU
Wheel: Nylon
Tread: PU
(Including B)



AU
Wheel: Aluminum
Tread: PU
(Including B)



UWE
Wheel: Steel
Tread: Antistatic PU
(Including B)



PH
Wheel: Heat Resistant Phenol
Tread: Heat Resistant Phenol