

Wheel Diameter (D[mm])	Product No.	Wheel Material	Load Capacity [daN (kgf)]	Wheel Width (W[mm])	Mounting Height (H[mm])	Mounting Base (A×B[mm])	Mounting Dimensions (X×Y (X'×Y') [mm])	Hole Diameter (P[mm])		
150	WK-150	Rubber(Including B)	200(204.0)	40	198	137×93	100×56	11		
	NRK-150									
	WEK-150	Conductive Rubber(Including B)								
	WOK-150	Oil Resistant Rubber(Including B)								
	WK-150-G	Grey Rubber(Including B)								
	NRK-150-G									
	MCBK-150	Monomer Cast Nylon(Including B)								
	UWK-150	PU(Including B)							300(306.0)	38
	GUK-150								200(204.0)	40
	UWEK-150	Antistatic PU(Including B)							300(306.0)	38
PHK-150	Heat Resistant Phenol	200(204.0)	40							
200	WK-200	Rubber(Including B)	250(255.0)	43	250	151×102	112×63	11.5		
	WEK-200	Conductive Rubber(Including B)								
	WOK-200	Oil Resistant Rubber(Including B)								
	WK-200-G	Grey Rubber(Including B)								
	MCBK-200	Monomer Cast Nylon(Including B)								
	UWK-200	PU(Including B)							400(408.0)	42
	GUK-200								250(255.0)	43
	UWEK-200	Antistatic PU(Including B)							400(408.0)	42
250	AWK-250	Rubber(Including B)	400(408.0)	60	305	200×140	140×80	14		
	AUK-250	PU(Including B)	600(612.0)	45						

Light Duty  
LIGHTSTAR

Medium Duty  
MIDDLESTAR

Heavy Duty  
HEAVYSTAR

Low-Profile Heavy Duty  
SHORTSTAR

Leveling  
LOCKSTAR

Stainless Steel  
STAINLESTAR

Towing  
LEADSTAR

Shock Absorbing  
SMOOSTAR

Silence  
SILENTSTAR

Office Equipment  
OFFICESTAR

