







固定式キャスター

※写真は代表的な製品イメージです。

ご注文例

L-type

E-type

M-type

S-type

J-type

H-type

AF-type

NP-type

SKY-type

SILENT-type

OTHER





150 | GUB | ,|PC(Y) 車輪径 車輪 カバー





▼ 併用できる





ŀ	PMR-LB[L]型IPC	
	P.108	

6			S							
車輪径 D(mm)	品番	車輪材質	許容荷重 [daN(kgf)]	車幅 W(mm)	取付高 H(mm)	取付座 A×B(mm)	取付寸法 X×Y(X'×Y') (mm)	穴径 P(mm)	偏心 E(mm)	旋回半径 R(mm)
	PMS-150WB,IPC(Y)	ゴム(B入)	200(204.0)	40	40 42 38 40 38 42	120×120	94×94 (87×87)	11	40	126
	PMS-150AW,IPC(Y)	耐摩耗ゴム(B入)	250(255.0) 42	42						
150	PMS-150UWB/INJ,IPC(Y)		300(306.0)	38						
150	PMS-150GUB,IPC(Y)	・ウレタン(B入)	250(255.0)	40						
	PMS-150APU,IPC(Y)	プレミアムウレタン(B入)	300(306.0)	38						
	PMS-150AUU,IPC(Y)	アルティメットウレタン(B入)	タン(B入) 350(357.0)	42						
	PMS-200WB,IPC(Y)	ゴム(B入)	250(255.0)	43	250	144×144	120×120 (105×105)	11.5	56	166
	PMS-200AW,IPC(Y)	耐摩耗ゴム(B入)	350(357.0)	45						
200	PMS-200UWB/INJ,IPC(Y)	- ウレタン(B入)	400(408.0)	42						
200	PMS-200GUB,IPC(Y)	(BX)	350(357.0)	43						
	PMS-200APU,IPC(Y)	プレミアムウレタン(B入) アルティメットウレタン(B入)	400(408.0)	45						
	PMS-200AUU,IPC(Y)		400(406.0)	45						

PMS型IPCカバー外形

	サイズ	幅(mm)	奥行(mm)	高さ(mm)	有効傾斜角			
	φ150用	170.8	64.4	90	15°*			
	φ200用	220.8	65.6	105	10°*			



※路面・走行の状態によってはカバーと路面が干渉する恐れがあります。





















ウレタン(B入)