

G-type G型 / G-S型 / GR型 / GRE型

車輪品番	車輪	車輪径 (mm)	許容荷重 [daN(kgf)]	ボス幅 (mm)	車幅 (mm)	車輪穴径 (mm)
L-25EL	 エラストマー	25	8(8.2)	14	12	4.7
L-32EL		32	12(12.2)	16	14	5.2
L-38EL		38	20(20.4)	20	17	6.2
L-50EL		50	25(25.5)	24	20	
S-65EL		65	40(40.8)	30	27	8.2
S-75EL		75	50(51.0)			
L-25R		25	8(8.2)	14	12	4.7
L-32R	 ゴム	32	12(12.2)	16	14	5.2
L-38R		38	20(20.4)	20	17	6.2
L-40R		40	40(40.8)			
L-50R		50	30(30.6)	24	20	
S-65RH		65	40(40.8)	30	25	8.2
S-75RH		75	50(51.0)			
L-25N	 ナイロン	25	10(10.2)	14	12	4.7
L-32N		32	18(18.4)	16	14	5.2
L-38N		38	28(28.6)	20	16	6.2
L-40N		40	40(40.8)	19	18	
L-50N		50	38(38.8)	24	21	
S-65N		65	55(56.1)	30	25	8.2
S-75N		75	65(66.3)			
L-25BN	 ナイロン(黒)	25	10(10.2)	14	12	4.7
L-32BN		32	18(18.4)	16	14	5.2
L-38BN		38	28(28.6)	20	16	6.2
L-50BN		50	38(38.8)	24	21	
S-65BN		65	55(56.1)	30	25	8.2
S-75BN		75	65(66.3)			
L-25UR	 ウレタン (ナイロンホイル)	25	10(10.2)	14	12	4.7
L-32UR		32	18(18.4)	16	14	5.2
L-38UR		38	28(28.6)	20	16	6.2
L-50UR		50	38(38.8)	24	21	
S-65UR		65	55(56.1)	30	25	8.2
S-75UR		75	65(66.3)			
L-25PC-C	 ポリカーボネート (透明)	25	10(10.2)	14	12	4.7
L-38PC-C		38	28(28.6)	20	16	6.2
L-50PC-C		50	38(38.8)	24.5	21.5	
L-25PC-R	 ポリカーボネート (赤)	25	10(10.2)	14	12	4.7
L-38PC-R		38	28(28.6)	20	16	6.2
L-50PC-R		50	38(38.8)	24.5	21.5	
L-25PC-G	 ポリカーボネート (緑)	25	10(10.2)	14	12	4.7
L-38PC-G		38	28(28.6)	20	16	6.2
L-50PC-G		50	38(38.8)	24.5	21.5	

※許容荷重は取付ける金具により異なります。 ※(B入)はペアリング入り車輪を表しています。