

H-type

HG-W型 / HR-W型 / HG型 / HG-S型 / HR型 / HT型 / HT-S型

車輪品番	車輪	 車輪径 (mm)	 許容荷重 [daN(kgf)]	 ポス幅 (mm)	 車幅 (mm)	 車輪穴径 (mm)
H-65GNB	 強化ナイロン (B入)	65	300(306.0)	42	38	12
H-75GNB		75	320(326.4)			
S-50MC	 モノマーキャストナイロン	50	160(163.2)	30	25	8.2
H-65MC	 モノマーキャストナイロン (B入)	65	300(306.0)	42	38	12
H-75MC		75	320(326.4)			
S-50MCE	 導電性モノマーキャストナイロン	50	160(163.2)	30	25	8.2
H-65MCE	 導電性モノマーキャストナイロン (B入)	65	300(306.0)	42	38	12
H-75MCE		75	320(326.4)			
H-65AU	 ウレタン (アルミホイル、B入)	65	300(306.0)	42	38	12
H-75AU		75	320(326.4)			
H-65PB	 フェノール (B入)	65	300(306.0)	42	38	12
H-75PB		75	320(326.4)			

車輪

H-type

HSG型 / HSG-S型 / HSR型

車輪品番	車輪	 車輪径 (mm)	 許容荷重 [daN(kgf)]	 ポス幅 (mm)	 車幅 (mm)	 車輪穴径 (mm)
UH-50GFB(φ12)	 強化ナイロン (B入)	50	300(306.0)	42	38	12
H-65GNB	 強化ナイロン (B入)	65	300(306.0)	42	38	12
H-75GNB		75				
H-50MC	 モノマーキャストナイロン (B入)	50	300(306.0)	42	38	12
H-65MC		65				
H-75MC		75				
H-50MCE	 導電性モノマーキャストナイロン (B入)	50	300(306.0)	42	38	12
H-65MCE		65				
H-75MCE		75				
H-50AU	 ウレタン (アルミホイル、B入)	50	300(306.0)	42	38	12
H-65AU		65				
H-75AU		75				
H-50PB	 フェノール (B入)	50	300(306.0)	42	38	12
H-65PB		65				
H-75PB		75				

*許容荷重は取付ける金具により異なります。 * (B入)はベアリング入り車輪を表しています。