


B-type

BP型

車輪品番	車輪	 車輪径 (mm)	 許容荷重 [daN(kgf)]	 ボス幅 (mm)	 車幅 (mm)	 車輪穴径 (mm)
B-125RHKP	 ゴム (ナイロンホイール、B入)	125	100(102.0)	38.4	34	12
B-125RHGP		125	100(102.0)	38.4	34	12

AF-type

E-AF型 / ER-AF型 / SPLG型 / SGW-AF型 / SR-AF型 / AF型 / HG-AF型

車輪品番	車輪	 車輪径 (mm)	 許容荷重 [daN(kgf)]	 ボス幅 (mm)	 車幅 (mm)	 車輪穴径 (mm)	
L-50R	 ゴム	50	30	24	20	6.2	
L-40BN(B24)		40	60(61.2)	24	21	6.2	
L-50BN		50	80(81.6)				
S-50BN	 ナイロン(黒)	50	60(61.2)	30	28	8.2	
S-65BN		65					
S-75BN		75					
S-60GN	 ナイロン(グレー)	60	130(132.6)	30	25	8.2	
NB-50		 強化ナイロン (B入)	50	250(255.0)	56	45	12
NB-65			65				
H-65GNB	 強化ナイロン (B入)	65	300(306.0)	42	38	12	
H-75GNB		75	320(326.4)				
H-65MC	 モノマーキャストナイロン (B入)	65	300(306.0)	42	38	12	
H-75MC		75	320(326.4)				
AF-75MC	 モノマーキャストナイロン (B入)	75	300(306.0)	56	45	12	
AF-100MC		100					
H-65MCE	 導電性モノマーキャストナイロン (B入)	65	300(306.0)	42	38	12	
H-75MCE		75	320(326.4)				
H-65AU	 ウレタン (アルミホイール、B入)	65	300(306.0)	42	38	12	
H-75AU		75	320(326.4)				
H-65PB	 フェノール (B入)	65	300(306.0)	42	38	12	
H-75PB		75	320(326.4)				

※許容荷重は取付ける金具により異なります。 ※(B入)はベアリング入り車輪を表しています。